



High-Speed All-in-One
A4 Color Devices

IM C530FB

Copier Printer Facsimile Scanner

RICOH
imagine. change.



Prepare your processes for the future

Do you want your team to work faster without compromising quality? You won't have to organize another "time management" course. There's a much smarter way to increase productivity in the 2020s.

Introducing the IM C530FB and IM C530F: the line of compact, high-speed, all-in-one devices that quickly handle all the most tedious tasks in an instant. This means your team can focus on the areas and tasks that allow them to get their work done... instead of having to wait for that 87-page report to print without paper jams.

Our new A4 color printers are specifically designed to efficiently and effectively increase your team's productivity. The IM C530FB (base model) and IM C530F (model with finisher) optimize digital workflows with cloud-based applications and solutions. As a result, all your processes can run smoothly, without costly disruptions or wait times.

- Work faster: Print seamlessly at up to 53 pages per minute, reduce wait times, and increase productivity.
- Optimize digital workflows: Instantly share and access all types of information, thanks to the multifunction printer's cloud connectivity.
- Grow at your own pace: Customize, manage, and easily add new features to your device using the new 7" touchscreen control panel.
- Save space: The IM C530FB and IM C530F are compact devices designed to take up less space, leaving more room for your most urgent needs.
- Print seamlessly: Print up to 3,250 sheets without interruption, making printing tasks more efficient.
- Fast and intuitive operation: The 7" Smart Operation Panel ensures a smooth and consistent user experience across multiple devices in our product lineup—just follow the on-screen steps.

Think about everything you can do in just seconds with your smartphone. Now imagine what your team could achieve with the IM C530FB—high-speed, all-in-one printers designed to significantly optimize your workflows and boost productivity.



Contact : 908 597 0184



copysan copiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083

Optimize your workflows and boost productivity effortlessly.

High-Speed A4 Color Printing

The IM C530FB and IM C530F, with their built-in finishing function, can print seamlessly at up to 53 pages per minute and deliver up to 3,250 pages without compromising quality, thanks to the new high-capacity tray. The user interface ensures a consistent experience across multiple devices in our product lineup, so once you've learned to operate one device, you can easily use any of them without effort.



Fully Digital Workflows = Seamless Processes

Today's fast-paced work environments require you to stay connected and meet expectations as quickly as possible.

The IM C530FB and IM C530F give you a competitive edge in this digital era with user-friendly workflow applications that seamlessly connect your printer to your preferred cloud-based services.

Additionally, these devices enhance security by restricting access to printed documents only to their owners, thanks to the exclusive Streamline NX secure release function. This gives you complete control over who can access your documents—whether it's your team members or clients.

Long-Lasting Technology to Drive Your Business Growth

There's no need to constantly upgrade your devices to access new features and functionalities. With our Always Current Technology platform, you'll receive the latest updates instantly, keeping you one step ahead.

The IM C530FB and IM C530F allow you to download and install the latest software features, applications, and updates directly on your device whenever you need them. This way, you can quickly adapt to your business's ever-evolving needs. You'll never have to wait for new functionalities to stay aligned with your business plans. Now, you can seamlessly guide your company's growth into the future.



Contact : 908 597 0184



copysan copiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083

Product Configuration

Mainframe

Internal Finisher SR1020 (for IM C530F only)

Stack capacity: 500 sheets
Staple capacity: 50 sheets
Dimensions: 450.8 x 477.6 x 248 mm
Weight: 7 kg

IM C530F



7" Smart Operation Panel
100-sheet SPDF
550-sheet input tray
150-sheet bypass tray
500-sheet output tray
Weight: 42 kg
Dimensions: 470 x 502.8 x 843.7 mm

IM C530FB



7" Smart Operation Panel
100-sheet SPDF
550-sheet input tray
150-sheet bypass tray
400-sheet output tray
Weight: 38 kg
Dimensions: 470 x 502.8 x 643.7 mm

Minimum space requirements

Front: 514 mm
Left: 100 mm
Right: 350 mm
Rear: 305 mm
Top: 234 mm

Other options

- IEEE 802.11 Interface Unit Type M43
- NFC Card Reader Type M43
- Unicode Font Package for SAP 1 Licence
- Unicode Font Package for SAP 10 Licence
- Counter Interface Type M12
- Medium Cabinet 76
- Low Cabinet 75
- Caster Table 74

Paper Feed Unit PB1180



Capacity: 550 sheets
Dimensions: 420 x 464.5 x 123 mm
Weight: 6.5 kg

LCT PB1190



Capacity: 2,000 sheets
Dimensions: 724.2 x 772.1 x 459 mm
Weight: 32.4 kg

Dimensions are stated in width x depth x height (W x D x H)



Contact : 908 597 0184



copsancopiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083

IM C530F/IM C530FB MAIN SPECIFICATIONS

	IM C530FB	IM C530F
GENERAL		
Configuration	Desktop	
Printing Process	Dry two-component electrophotographic printing	
Development	Non-magnetic, single-component development	
Technology	Electro photographic printing system with laser beam	
Warm-up Time	39 Seconds	
First Page Out Speed: B/W	4 Seconds	
First Page Out Speed: Color	4,2 Seconds	
Continuous Printing Speed	53 ppm	
Memory: Standard	2 GB	
Memory: Maximum	2 GB	
Storage	eMMC: 32GB	
SPDF Capacity	100 Sheets	
Duty Cycle	150.000	
Duplex	Yes	
Weight	38 kg	42 kg
Dimensions (W x D x H)	470 x 502,8 x 643,7 mm	470 x 502,8 x 843,7 mm
Power Supply	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz
COPIER		
First Copy Speed	B/N: 6,5 Seconds Color: 6,6 Seconds	
Multiple Copy	Up to 999 copies	
Resolution	1.200 x 1.200 dpi	
Color Mode Adjustment	Default: Black and White mode Automatic Color Selection (ACS) Full color Black and white One color:	
Reproduction Scale	400%, 200%, 155%, 141%, 129%, 122%, 121%, 115%, 100%, 93%, 85%, 82%, 78%, 75%, 73%, 71%, 65%, 50%, 25%	
Maximum Original Size	Libro: A3, DLT, A4 ADF: A3, DLT, A4	
Zoom	Del 25 % al 400 % en incrementos del 1 %	
Paper Selection	1 st Tray 2 nd Tray 3rd Tray (with paper bank) (Optional) 4rd Tray (with paper bank) (Optional) Bandeja bypass LCT	
IMPRESORA		
CPU	ARM CortexA53 - Dual core 1,2 GHz	
Printer Language: Standard	PCL5c, PCL6, PostScript 3 (emulation), Direct PDF Printing (emulation)	
Resolution: Maximum	1.200 x 1.200 dpi	
Print Resolution	PCL5c: 300 dpi, 600 dpi PCL6: 600 dpi, 1.200 dpi, 1.200 dpi PS3: 600 dpi, 1.200 dpi, 1.200 dpi	
Standard Interface	Mainframe (Ethernet (1000BASE-T/100BASE-TX/10BASE-T), USB 2.0, USB Host 2.0 (3G dongle only), Fax), Bluetooth 4.2, SD card slot (1 slot / supports SDHC memory card), USB host (Type A: 1 port / supports USB flash memory), optional USB host (Type A: 1 port / supports keyboard), optional USB host (Type Mini B: 1 port / supports NFC IC card R/W), MicroSD card slot for ROM storage expansion of the operating unit, wireless LAN (IEEE 802.11 a/b/g/n), NFC tag (includes: ISO14443 Type A, NFC Tag Forum Type 2 compatible). Options: Wireless LAN (IEEE 802.11a/b/g/n).	
Mobile Printing Capability	Apple AirPrint, Mopria®, Google Cloud Print, Ricoh Smart Device Connector.	
Environments: Windows®	Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008 R2, Windows® Server 2012 R2, Windows® Server 2016.	
Environments Mac OS	Macintosh 8.6 or later (OS X Classic), Macintosh OS X v10.12 or later	
UNIX Environments	Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServer (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX (V6.1, V7.1, V7.2), Citrix XenApp (7.15 or later).	
SAP® Environments	SAP® R/3®, SAP® R/4®.	
Network/Operating System	PCL5c: Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Server 2008 (32/64-bit), Server 2008R2 (64-bit), Server 2012/R2 (64-bit), Server 2016, SAP R/3, SAP R/4, Unix Sun Solaris, HP-UX, SCO OpenServer, Red Hat Linux, IBM AIX. PCL6: Windows 7 (32/64-bit), Server 2008 (32/64-bit), Server 2008R2 (64-bit), Windows 8.1 (32/64-bit), Server 2012/R2 (64-bit), Windows 10 (32/64-bit), Server 2016. PS3: Windows 7 (32/64-bit), Server 2008 (32/64-bit), Server 2008R2 (64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Server 2012/R2 (64-bit), Server 2016, Unix Sun Solaris, HP-UX, SCO OpenServer, Red Hat Linux, IBM AIX.	



Contact : 908 597 0184



copysan Copiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083

IM C530F/IM C530FB

MAIN SPECIFICATIONS

IM C530FB

IM C530F

SCANNER

CIS	Scanning: Full color (opm)
Scanning Speed: SPDF	Duplex: BW (71 ipm (A4, 200dpi)), Color (52 ipm (A4, 200dpi))
Resolution: Maximum	600 dpi
Scanning Resolution	Standard: 100 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi Default: 200 dpi
Compression Method	BW: TIFF (MH, MR, MMR, JBIG2), Grayscale Color: JPEG
File Formats	Single-page TIFF (Compression enabled, Compression disabled), Single-page JPEG (Compression enabled), Single-page PDF (Compression enabled, Compression disabled), High compression single-page PDF (Compression enabled), Single-page PDF-A (Compression enabled, Compression disabled), Multi-page TIFF (Compression enabled, Compression disabled), Multi-page PDF (Compression enabled, Compression disabled), High compression multi-page PDF (Compression enabled), Multi-page PDF-A (Compression enabled, Compression disabled).
Scan Destinations	Email, Folder, USB, SD Card
Scan Area:	215,9 mm
Main scan area	
Scan Area:	SPDF (405,6 mm), Book
Secondary scan area	
Network TWAIN	SO:Server2008(32bit)/7(32bit)/8.1(32bit)/10(32bit), Server2008(64bit)/7(64bit)/8.1(64bit)/10(64bit)/Server2008R2(64bit)/Server2012(64bit)/Server2012R2(64bit)/Server2016(64bit)/Server2019(64bit) Resolución: B/W (Book, ARDF) Color (Book, ARDF) Scan Mode: Standard/Photograph/OCR/Archiving Image Adjustment: Brightness/Contrast/Threshold/Gamma Adjustment/ Halftone Pattern Endorser: Date/Page Number/Text
Scan Mode (B/W)	Text/Line B/W, Text B/W, Text/Photo B/W, Photo B/W, Grayscale B/W
Scan Mode (Color)	Text/Photo Color, Glossy Photo Color, Auto Color Selection
Image Density	Automatic/Manual: Yes (adjustable with 7 steps)
SADF / modo lotes	yes
Email Address Search Method on HDD	Name, Email Address

FAX

Circuit	PSTN, PBX
Transmission Speed	G3: Approximately 3 seconds (200 x 100 dpi, JBIG, ITU No. 1 graphic TTI disabled, memory transmission)
Modem Speed: Maximum	33,6 Kbps
Resolution: Standard	8x3.85 lines/mm, 200x100 dpi 8x7.7 lines/mm, 200x200 dpi
Compression Method	MH, MR, MMR
Scanning Speed	46 spm
Page Memory Size	Standard: 9.7 MB
SAF Memory Size	Standard: 4 MB (approximately 320 pages)
SID Code (Sender ID)	yes
OMR Scheduling (Optical Mark Recognition)	No
Phone Specifications	Headset/Telephone Monitor Speaker On-Hook Dialing Tone Transmission Pause Tone/Pulse Selection Receive Mode Selection Auto-Answer Delay Time Busy Line Tone Detection

Paper Management

Recommended Paper Size	Standard Paper Tray(s): (A4, A5, B5, Legal, Letter, Half Letter, Executive, Foolscap, Monarch, C5, DL Envelope) Optional Paper Tray(s): (A4, A5, B5, Legal, Letter, Half Letter, Executive, Foolscap, C5, Envelopes)LCT: (A4) Bypass Tray: (A4, A5, A6, B5, Legal, Letter, Half Letter, Executive, Foolscap, Monarch, C5, C6, DL Envelope, Custom Paper Size)		
Standard Input Capacity	550 Sheets		
Paper Input: Bypass Tray	150 Sheets		
Paper Input: Optional Tray	Paper Bank Unit: 550 sheets LCT: 2.000 Sheets 3,250 sheets		
Maximum Input Capacity	3,250 sheets		
Standard Output Capacity	400 Sheets		500 Sheets
Paper Weight: 60 - 220 g/m ²	60 - 220 g/m ²		-
Paper Weight (Optional Trays):	60-176 g/m ²		60 - 220 g/m ²
	60 - 220 g/m ²		60-176 g/m ²
	60 - 176 g/m ²		60 - 220 g/m ²
Paper Weight (Optional Tray - LCT)			60 - 176 g/m ²
Paper Weight (Bypass Tray):			
Paper Weight (Duplex):			
Paper Types	Plain Paper, Recycled Paper, Special Paper 1-3, Letterhead, Envelope, Coated Paper, Medium Heavy Paper, Heavy Paper 1, Heavy Paper 2		



Contact : 908 597 0184



copysancopiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083

IM C530F/IM C530FB

MAIN SPECIFICATIONS

	IM C530FB	IM C530F
Authentication		
Windows Authentication		
LDAP Authentication		SI, Kerberos (SI)
Security Features		
Encryption	Password Authentication Encryption, SSL Communication, SMTP over SSL/TLS, Transport Layer Security (TLS), Wireless LAN (WEP), Wireless LAN (WPA), Wireless LAN (11i)	
Others	Network Protocol Act./Deact., IP Filter (Access Control), Mask Type for Copy/Data Security Copy, Option for Data Security Copy Unit	
Environment		
Power Consumption: Maximum	Less than 1,650 W	
Power Consumption during Operation: B/W	578 W	
Power Consumption during Operation: Color	633 W	
Power Consumption: Ready	99,8 W	
Power Consumption: In standby	0,75 W	
TEC*	Power Consumption: 0.73 kWh/week	
Sound	Acoustic Power Level:	
	In Standby/Power Save Mode (30 dB/30.4 dB), Printing (dB), Copying (Nominal Value)	
	Sound Pressure Level: In Standby/Power Save Mode (dB), Printing (dB)	



Contact : 908 597 0184



copysan copiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083