

RICOH IM C4500 IM C6000

Copier Printer Facsimile Scanne



11" x 17" Multifunction Color

Work smarter and more effectively with the range of RICOH IM C4500/IM C6000 intelligent devices, technology designed to grow and adapt alongside your business.

It's time to:

- Work smarter: by using integrated workflow scanning processes.
- Personalize your experience: with easy access to the apps you use most often.
- Stay up to date: by adding new features as needed.
- Save costs: by reducing energy and paper consumption.

Gain access to essential feature upgrades and updates whenever you need them. Boost productivity by seamlessly integrating applications from our secure application site to optimize and streamline your workflow. Trust that your intelligent devices are ready to meet all your demands, now and in the future, with technology that is scalable, secure, sustainable, and simple.



Contact : 908 597 0184



copysan copiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083



Get more from your intelligent device:
Save time and streamline workflows with
the right finishing solution for every task.
Enhance print management with
the Color Controller E-25C.

Take advantage of a variety of finishing and paper options to add a professional touch while meeting the printing demands of medium to large workgroups.

Low TEC (Typical Electricity Consumption) values reduce energy consumption and lower running costs. RICOH Intelligent Support tools ensure maximum uptime for your device, while self-help tools empower your teams to make simple adjustments, such as changing supplies, without needing costly IT resources.



Contact : 908 597 0184



copysan copiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083

RICOH IM C4500/IM C6000

MAIN SPECIFICATIONS

	IM C4500	IM C6000
GENERAL		
Warm-up time		21 seconds
First output speed: B/W	3.6 seconds	2.9 seconds
First output speed: full color	5.4 seconds	4.2 seconds
Continuous output speed	45 ppm	60 ppm
Memory: standard		2 GB
Memory: maximum		4 GB
HDD: standard		320 GB
HDD: maximum		320 GB
SPDF capacity		220 sheets
Weight		223.5 lbs / 101.4 kg
Dimensions: W x D x H		23.1" x 27" x 37.9"
Power source		120V - 127V 60Hz
COPIER (STANDARD)		
Multiple copying		Up to 999 copies
Resolution		600 dpi
Zoom		From 25% to 400% in 1% steps
PRINTER (STANDARD)		
CPU		Intel Apollo Lake 1.6GHz
Printer language: standard		PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)
Printer language: option		Genuine Adobe [®] PostScript [®] 3™, IPDS, PDF Direct from Adobe [®]
Print resolution		Up to 1,200 x 1,200 dpi
Network interface: standard		Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B
Network interface: option		Wireless LAN (IEEE 802.11a/b/g/n)
Mobile printing capability		Apple AirPrint [®] , Mopria [®] , NFC, RICOH Smart Device Connector
Windows [®] environments		Windows [®] 8.1, Windows [®] 10, Windows [®] Server 2012R2, Windows [®] Server 2016, Windows Server 2019
Mac OS environments		Macintosh OS X v10.11 or later
UNIX environments		UNIX Sun [®] , Solaris, HP-UX, SCO OpenServer, RedHat [®] , Linux Enterprise, IBM [®] AIX
SAP [®] environments		SAP [®] R/3 [®] , S/4 [®]
Other supported environments		IBM iSeries AS/400 using OS/400 Host Print Transform
SCANNER (STANDARD)		
Scanning speed		120 ipm (simplex) / 240 ipm (duplex)
Resolution: maximum		Up to 1,200 dpi
Compression method		TIFF (MH, MR, MMR, JBIG2), Grayscale
File formats		Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encryption PDF, OCR* Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encryption PDF, OCR* * Requires optional OCR Unit Type M13
Scan modes		E-mail, Folder, USB, SD Card
FACSIMILE (OPTIONAL)		
Circuit		PSTN, PBX
Transmission speed		2 seconds (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission)
Modem speed: maximum		33.6 Kbps
Resolution: standard		8 x 3.85 line/mm, 200 x 100 dpi
Resolution: option		16 x 15.4 line/mm, 400 x 400 dpi
Compression method		MH, MR, MMR, JBIG
Scanning speed		81 spm (A4/LT LEF Image Rotation)
Memory: standard		4 MB (320 pages)
Memory: maximum		60 MB (4,800 pages)
PAPER HANDLING		
Recommended paper size		Tray 1: 8-1/2" x 11" (A4) Tray 2: 5-1/2" x 8" - 12" x 18" (SRA3, A3 - A6, B4 - B6), Envelopes Bypass tray: Up to 12" x 18", Envelopes, Custom Sizes [Width: 3.5" - 12.6" (90 - 320 mm), Length: 5.8" - 49.6" (148 - 1260 mm)]
Paper input: standard		1,200 sheets
Paper input: maximum		4,700 sheets
Paper output: standard		500 sheets 8.5" x 11" (A4) or smaller; 250 sheets (B4) or larger
Paper output: maximum		3,625 sheets
Paper weight		Trays: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m ²) Bypass: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²) Duplex: 14 - 68 lb. Bond/142 lb. Index (52 - 256 g/m ²)
Paper types		Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP, Gloss
ECOLOGY		
Power consumption: maximum		Less than 1,584 W
Power consumption operation: B/W	619.7 W	822.5 W
Power consumption operation: full color	704.6 W	938.2 W
Power consumption: ready		54.3 W
Power consumption: sleep		0.59 W
TEC ¹	0.51 kWh	0.76 kWh
ENERGY STAR [®]		Certified
EPEAT [®]		Gold Rated*
		* EPEAT Gold rating is applicable only in the USA.



Contact : 908 597 0184



copysan copiers@gmail.com



1406 Stuyvesant Ave
Union, NJ 07083